

2000/G LEGEND MID BOOT

POLICE & MILITARY



LEATHER TRANSPARATION
+500%

LONG LASTING SOLE
+20%

SOLE BONDING STRENGTH
+80%

HEEL ENERGY ABSORPTION
+80%

- Police footwear
- New shape with a larger metatarsal area with accentuation of the heel's curve as for the arch of instep area.
- Lightweight and comfortable
- Good stability both for walking and running
- Lining: GORE-TEX® Performance Comfort footwear, excellent for various climate conditions and for outdoor activities
- Highly breathable (breathability is 500% higher than the European Standard EN ISO 20347 5.4.6 requirement)
- Extremely comfortable for long-day usage
- Nitrile rubber sole with excellent grip on uneven grounds (the outsole is 20% more durable than the European Standard EN ISO 20347 5.8.3 requirement)
- The sole bonding strength is 80% higher than the European Standard EN ISO 20347 5.3.1.2 requirements
- The energy absorption in the heel area is 80% higher than the European Standard EN ISO 20347 6.2.4 requirements
- Antistatic outsole resistant to fuel oil. Cleated tread



Product name: LEGEND MID SHOE	positioned a polymeric material shank hold by a plastic reinforcement extending for 75% of the bottom surface.
Article number: 2000/G	
Leather upper	Sole
Black full-grain cowhide leather, 1.8 - 2.0 mm thick, water-repellent, breathable treated, chrome-tanned and aniline dyed	Rubber sole, antistatic, oil and petrol resistant, with shock-absorbent heel. Resistant to contact heat (tested at 300°C) and non slip SRC.
Top lining	Weight/pair
Soft black full-grain leather, 1.1 - 1.2 mm thick, water-repellent, breathable treated, chrome-tanned and aniline dyed	abt 1290 g (size 42)
Lining	Back height
Seam sealed 4 ply laminate (GORE-TEX® DURACOM MS SPORTIVE), bootie construction: Layer 1 - Warp knit 72%PA / 28% PES Layer 2 - Functional non-woven 100% PES Layer 3 - Bicomponent membrane based on ePTFE Layer 4 - Backing fabric knit 100% PA	abt 15 cm (sole included) (size 42)
Toe cap	CE certificate
1.3 mm resinated synthetic bonded fabric, thermally mouldable.	EN ISO 20347:2012 O2 CI HRO HI WR FO - SRC Category II P.P.E.
Heel cap	Size range
1.8 mm resinated synthetic bonded fabric, thermally mouldable.	36 - 49
Sewing thread	
Polyester 20/3, black, water-repellent treated	
Lacing system	
Round polyester laces, black, water-repellent treated, passing through 5 couples of rustproof burnished brass eyelets	
Foot-bed	
Anatomically shaped, 3,5 mm thick, made out of a layer of nonwoven material to absorb exceeding humidity, and with an upper covering made of anti abrasion nonwoven 100% PA.	
Insole	
Antistatic cellulose fibre, elastomeric bonded, 4.0 mm thick. In the heel area is	

