

2005/G LEGEND LOW SHOE

POLICE & MILITARY



LEATHER TRANSPARATION
+500%

LONG LASTING SOLE
+20%

SOLE BONDING STRENGTH
+80%

HEEL ENERGY ABSORPTION
+80%

- Lightweight and comfortable police shoe
- New shape with a larger metatarsal area with accentuation of the heel's curve as for the arch of instep area.
- Good stability both for walking and running
- Lining: GORE-TEX® Performance Comfort footwear, excellent for various climate conditions and for outdoor activities
- Highly breathable (breathability is 500% better than the European Standard EN ISO 20347 5.4.6 requirement)
- Extremely comfortable for long-day usage
- Excellent grip on uneven grounds (the outsole is 20% more durable than the European Standard EN ISO 20347 5.8.3 requirement)
- The sole bonding strength is 80 % higher than the European Standard EN ISO 20347 5.3.1.2 requirements
- The energy absorption in the heel area is 80% higher than the European Standard EN20347 6.2.4 requirements
- Antistatic outsole resistant to fuel oil with cleated tread



Product name: LEGEND LOW SHOE	for 75% of the bottom surface.
Article number: 2005/G	Sole
Leather upper	Rubber sole, antistatic, oil and petrol resistant, with shock-absorbent heel. Resistant to contact heat (tested at 300°C) and non slip SRC.
Black full-grain cowhide leather, 1.8 - 2.0 mm thick, water-repellent, breathable treated, chrome-tanned and aniline dyed	Weight/pair
Top lining	abt 1180 g (size 42)
Soft black full-grain leather, 1.1 - 1.2 mm thick, water-repellent, breathable treated, chrome-tanned and aniline dyed	Back height
Lining	abt 11 cm (sole included) (size 42)
Seam sealed 4 ply laminate (GORE-TEX® DURACOM MS SPORTIVE), bootie construction: Layer 1 - Warp knit 72% PA / 28% PES Layer 2 - Functional no-woven 100% PES Layer 3 - Bicomponent membrane based on ePTFE Layer 4 - Backing fabric knit 100% PA	CE certificate
Toe cap	EN ISO 20347:2012 O2 CI HI HRO WR FO - SRC Category II P.P.E.
1.3 mm resinated synthetic bonded fabric, thermally mouldable.	Size range
Heel cap	36 - 49
1.8 mm resinated synthetic bonded fabric, thermally mouldable.	
Sewing thread	
Polyester 20/3, black, water-repellent treated	
Lacing system	
Round polyester laces, black, water-repellent treated, passing through 5 couples of rustproof burnished brass eyelets	
Foot-bed	
Anatomically shaped, 3,5 mm thick, made out of a layer of nonwoven material to absorb exceeding humidity, and with an upper covering made of anti abrasion nonwoven 100% PA.	
Insole	
Antistatic cellulose fibre, elastomeric bonded, 4.0 mm thick. In the heel area is positioned a polymeric material shank hold by a plastic reinforcement extending	